



Filter housing APF1300

Design / capacity		
Connection	Rp 3" NPT female thread	
Nominal capacity	1300 scfm with APE1300 at 14.5 psi (abs.) and 68°F at 101.5 psig	
Maximum capacity	1812.94 scfm with APE1300 at 14.5 psi (abs.) and 68°F at 232 psig	
Maximum working pressure	152.25 psig	
Material	Aluminum	
Operating temperature maximum	248 °F	
Coating inside / outside	Corrosion protection layer	
Colour outside	RAL 5010 (powder coated)	
Fixing element	Wing suspension	
Condensate drainage connection	Rp 1/2" female thread	
Dimensions in inch	A	35.39
[Dimension drawing on the last page]	B	2.20
	C	8.46
	D	8.27
Weight (incl. element and drainage)	47.08 lbs	
Norm	ASME B31.3;2020	

Scope of supply	
Housing	APF1300
Filter element	APE1300
Types of condensate drainage:	
VF25 – FF5 – MFO – MF1 – SMA	D150
DSF - DMF. CA	HAM12

Options		
Differential pressure gauge	APF-DPN	
Level-controlled condensate drain	KN1	
Level-controlled condensate drain	KN5	

Capacity filter elements APE1300

Type	Particle filtration	Residual oil content	Working temperature [Fahrenheit]		Differential pressure [psi]			ISO classes*	
	[micron]	[mg/m³]	maximum	recommended	new	moistened	replacement	particle	oil
APE1300CA	-	0.003	122	77	1.5	-	every 6 months	-	1
APE1300DMF	1	-	248	-	0.8	-	every 12 months	2	-
APE1300DSF	0.01	-	248	-	1.1	-	every 12 months	1	-
APE1300FF5	5	5	248	-	0.7	1.1	every 12 months	3	4
APE1300MF1	0.1	0.1	248	-	0.9	1.3	every 12 months	1	2
APE1300MFO	1	0.5	248	-	0.8	1.2	every 12 months	2	3
APE1300SMA	0.01	0.01	248	-	1.1	1.6	every 12 months	1	1
APE1300VF25	25	10	248	-	0.7	0.7	every 12 months	5	5

Compressed air filter APF1300 with filter element APE1300

Rev 01_1122



Filter elements APE1300 VF25 – FF5 – MFO – MF1 – SMA

Design	
Flow direction	From the inside out
Material end caps	Glass-fibre reinforced nylon (30%)
Support body inside and outside	Stainless steel
Filtration medium	Borosilicate microfiber fabric
Pre- and after filtration	Polypropylene netting
Drainage layer	Nonwoven polyester
Bonding end caps	Two-part epoxy resin
Material o-ring	NBR
Distinctive characteristics	Technically silicone-free
Cavity volume at 68°F	96%

Filter elements APE1300 CA

Design	
Flow direction	From the inside out
Material end caps	Glass-fibre reinforced nylon (30%) - (temperature resistant up to 248°F)
Support body inside and outside	Stainless steel
Filtration medium	Non-woven medium. activated carbon impregnated
After filtration	Borosilicate microfibre
Bonding end caps	Two-part epoxy resin
Material o-ring	NBR
Distinctive characteristics	Technically silicone-free
Cavity volume at 68°F	96%

Filter elements APE1300 DSF - DMF (dust filtration)

Design	
Flow direction	From the outside in
Material end caps	Glass-fibre reinforced nylon (30%) - (temperature resistant up to 248°F)
Support body inside and outside	Stainless steel
Filtration medium	Borosilicate microfiber
Pre- and after filtration	Polypropylene netting
Bonding end caps	Two-part epoxy resin
Material o-ring	NBR
Distinctive characteristics	Technically silicone-free
Cavity volume at 68°F	96%

Correction factors	
Working pressure	psig
	29 43.5 58 72.5 87 101.5 116 130.5 145 159.5 174 188.5 203 217.5 232
	Coefficient
	0.38 0.50 0.63 0.75 0.88 1.00 1.12 1.25 1.37 1.49 1.62 1.74 1.86 1.98 2.10

Multiply the capacity of the filter by the correction factor in the upper table.

